


# QUICK START GUIDE

## LIFETONE HL™ BEDSIDE FIRE ALARM AND CLOCK MODEL HLAC151 WITH EASY SETUP


Thank you for purchasing the Lifetone HL™ Bedside Fire Alarm and Clock. These items are included:



HLAC151



Bed Shaker



4 D-Cell Alkaline Batteries



HLAC151 User's Manual

# SETUP VIDEO




**IMPORTANT: PLACE THE LIFETONE HL™ NEXT TO YOUR BED, WITH THE SPEAKER FACING YOUR PILLOW.**

## STEP 1 - POWERING THE HLAC151™

1. Remove the battery door from the back of your HLAC151™.
2. Insert four D-cell alkaline batteries as shown in the illustration at right, matching the polarity signs (+ and -) in the open compartment. You should do this before plugging your HLAC151 into a wall outlet.
3. Replace the battery door securely. A flashing "TEST" on the screen tells you the batteries are installed correctly.
4. Plug the Lifetone HLAC151 into an electrical outlet near your bedside. Don't use an outlet that is controlled by a wall switch.
5. You may plug in the bed shaker now or at any time after setup.
6. The word "TEST" continues to flash on the screen. Go to STEP 2.

NOTE: The HLAC151 operates on AC power. The batteries are only for backup during electrical outages.




## STEP 2 - SETUP WITH YOUR SMOKE DETECTOR

Read and follow all the printed instructions below. The voice prompts supplement these instructions.

1. The word "TEST" is flashing on the screen and your HLAC151™ says, "Press the red button to begin." Press and release the red TEST/SILENCE button on the back.
2. "TEST" stops flashing and your HLAC151 says, "Please wait."
3. After about 30 seconds, "TEST" starts flashing again and your HLAC151 says, "At the tone, test your smoke alarm." This means it's time to press the test button on your smoke alarm.
4. Go to the most distant smoke alarm you want detected. If your alarms are interconnected, use the nearest one instead. Press and hold the test button on the smoke alarm until the Lifetone HL™ alarm sounds, indicating a successful setup test. Between two and six T3 cycles (groups of 3 beeps) of the smoke alarm will be required. You'll need to hold the smoke-alarm button down for 10 to 30 seconds.
5. If the test is not successful, try again using a nearer smoke alarm. You may try as many times as you like. Your HLAC151 will continue with this test until it is successful.
6. When the test is successful, the Lifetone HL™ alarm sounds and "FIRE" flashes on the screen. **IMPORTANT WARNING:** If you have First Alert alarms with voice, see section IV, OPERATING INSTRUCTIONS, in the HLAC151 User's Manual.
7. When the setup test has finished, the "12 hr" option for the time display appears on the screen and your HLAC151 says, "Now, set the clock." Go to STEP 3.

If the setup test has not been successful after several tries, the smoke alarm may not be issuing a T3 signal. See the section titled "TESTING THE LIFETONE HL™" in the User's Manual.

Press the TEST/SILENCE button to start the test.



Smoke alarm has been detected.




Successful test. You may now set the clock.

### STEP 3 - SETTING THE CLOCK

1. On the time display, "12 hr" appears. To select 24-hour time, press + or - .
2. Press SET CLOCK. The hour will flash. To change the hour, press + or - .
3. Press SET CLOCK. The minute will flash. To change the minute, press + or - .
4. Press SET CLOCK. The year will flash. To change the year, press + or - .
5. Press SET CLOCK. The small "M" and "D" will flash. To change to a day-first display of the date, press + or - .
6. Press SET CLOCK. The month will flash. To change the month, press + or - .
7. Press SET CLOCK. The day of the month will flash. To change the day, press + or - .
8. Press SET CLOCK. The "E" (for English) will flash. To change to Spanish ("S") or French ("F"), press + or - . Press SET CLOCK again.
9. The clock will show the day of the week to the right of the date. If you prefer to display the year instead, press SET CLOCK again.

NOTE: When you need to reset the clock, press and hold SET CLOCK until "12 hr" appears. Release the button, and then repeat all parts of STEP 3.

Buttons on the Top of the Lifetone HL™




### STEP 4 - SETTING THE WAKE-UP ALARM

1. If the wake-up hour isn't already flashing, press and hold SET ALARM. Release the button when the wake-up hour flashes. To change the hour, press + or - .
2. Press SET ALARM. The wake-up minute will flash. To change the minute, press + or - .
3. Press ON/OFF to enable or disable the wake-up alarm. The bell icon at lower left appears when the alarm is enabled and disappears when the alarm is disabled.

You can use the HI LO slide switch to adjust the volume of the wake-up alarm. The emergency alarm always sounds at full volume.

NOTE: To change the wake-up alarm time, press and hold SET ALARM until the wake-up hour flashes. Release the button, and then repeat all parts of STEP 4.





### ERROR MESSAGES

**Batteries:** If the clock is flashing "BATT" and beeping at one-minute intervals, the batteries were not installed correctly or are below the required voltage. Remove and reinsert them, or replace them if necessary. Be sure to match the polarity signs (+ and -) in the battery compartment. To keep the setup with your smoke alarm, leave the clock plugged in while you change batteries.

**Bed shaker:** If the screen is flashing "bedS" and the clock is beeping, the bed shaker has probably come unplugged. Seat the bed-shaker plug firmly into the jack.

NOTE: If you want to stop using the bed shaker after it has been installed, unplug it and then press and hold the red TEST/SILENCE button for 2 seconds. That starts a manual self-test that will display "TEST" for 10 to 20 seconds, sound the fire alarm briefly, and "retrain" the HL to operate without a bed shaker. If you decide to start using the bed shaker again, simply plug it in.



800 Research Parkway, Suite 339  
Oklahoma City, OK 73104

PLEASE READ THE USER'S MANUAL COMPLETELY AND THOROUGHLY FOR FURTHER DIRECTIONS, PRODUCT FEATURES, AND WARRANTY INFORMATION.

For more information, visit [www.lifetonesafety.com](http://www.lifetonesafety.com) or call 1-800-648-7923 (+1 405 200 1555 outside North America).

**MODEL HLAC151**

KEEP THIS QUICK-START GUIDE IN A SAFE PLACE

Doc# LTQSG151E131227