

Personal Sound Amplifier

HANDHELD SOUND AMPLIFIER

Microphone **Body Frame Material Max Output**

Humidity Operating Range Frequency Range

Frequency Switch Plug-in Connector Power Source USB Charger Operation Time

50dB, multi-element, integrated

High Impact ABS

107 dB

At 20°C. 95% RH Low: 25Hz - 3.5kHz Medium: 100Hz - 18kHz High: 900Hz - 25kHz 3-position, user selectable Stereo Jack, 3.5mm diameter Two AA Ni-MH batteries (included) 110/240VAC, USB to Mini-B jack

Approx. 40 hours per charge

HEADPHONES (SE-HP)

Mylar, diameter 30mm. Diaphragm Impedance 32 ohms +- 20% at 1kHz **Nominal Power** 20mW

Max Power 40mW

Sensitivity 100 dB S.P.L +- 2dB 1kHz

Balance per Channel +- 3 dB at 1kHz **Frequency Response** 20Hz-20kHz

Plug-in Connector Stereo Plug, 3.5mm diameter

Cord Length 1150mm - +-50mm

Weight 50g +-5g

Earpad Black, cushioned sponge

EARBUDS (LC-EB)

Diaphragm Mylar, diameter 10mm. **Impedance** 32 ohms +- 15% at 1kHz **Max Power** 10mW

Sensitivity 105 dB S.P.L +- 3dB 1kHz

Balance per Channel +- 3 dB at 1kHz **Frequency Response** 20Hz-20kHz 1kHz **Plug-in Connector** Stereo Plug, 3.5mm diameter

Cord Length 1150mm - +-50mm

THD Less than 5% at 1kHz 0.126V Weight

50g +-5g



HS TARIFF CODE: 8515.50

SE9000HP DETAILS

WARRANTY 3 year **MEASUREMENTS**

3.05"x 2"x 0.75" **CERTIFIED CE & ROHS COMPLIANT** CMS, MDS, ADA,

ACA 1557, Prop 65

Cleaning Instructions Available

CUBE AND USB CABLE ARE INCLUDED

LIGHTWEIGHT, PREMIUM QUALITY STEREO HEADPHONES AND EARBUDS BELT/POCKET CLIP INCLUDED







TACTILE

ON/OFF VOLUME CONTROL

WHEEL

SonicTechno Quality and Innovation since 1981

www.sonictechnology.com superear@sonictechnology.com