

SuperEar®

SE7500



HS TARIFF CODE: 8515.50

Personal Sound Amplifier

HANDHELD SOUND AMPLIFIER

Automatic Shut Off	Yes, 45 minutes
Microphone	50dB, integrated
Body Frame Material	High Impact ABS
Max Output	107 dB
Humidity Operating Range	At 20°C, 95% RH
Operating Temperature	0°C - 55°C
Frequency Range	100Hz - 14kHz
Plug-in Connector	Stereo Jack, 3.5mm diameter
Power Source	Two AAA Alkaline battery (included)
Weight	3 oz.
Belt/Pocket Clip	Included

HEADPHONES (SE-HP)

Diaphragm	Mylar, diameter 30mm.
Impedance	32 ohms +/- 20% at 1kHz
Nominal Power	20mW
Max Power	40mW
Sensitivity	100 dB S.P.L +/- 2dB 1kHz
Balance per Channel	+/- 3 dB at 1kHz
Frequency Response	20Hz-20kHz
Plug-in Connector	Stereo Plug, 3.5mm diameter
Cord Length	1150mm - +/-50mm
Weight	50g +/-5g
Earpad	Black, cushioned sponge

EARBUDS (LC-EB)

Diaphragm	Mylar, diameter 10mm.
Impedance	32 ohms +/- 15% at 1kHz
Nominal Power	5mW
Max Power	10mW
Sensitivity	105 dB S.P.L +/- 3dB 1kHz
Balance per Channel	+/- 3 dB at 1kHz
Frequency Response	20Hz-20kHz 1kHz
Plug-in Connector	Stereo Plug, 3.5mm diameter
Cord Length	1150mm - +/-50mm
THD	Less than 5% at 1kHz 0.126V
Weight	50g +/-5g

SE7500 DETAILS

WARRANTY	3 year
MEASUREMENTS	3.05" x 2" x 0.75"
CERTIFIED	CE & ROHS
COMPLIANT	CMS, MDS, ADA, ACA 1557, Prop 65

Cleaning instructions available



SonicTechnology
Quality and Innovation since 1981

www.sonictechnology.com
superear@sonictechnology.com

Use with Disposable Sanitary Earpad Covers
- Model EPC100

FAX 530-272-4257 | 1-800-247-5548
P.O. Box 539, Grass Valley, CA 95945

V1.1 11/21/19